

LiveCycle Forms ES

Form Output

Specify the output of HTML returned in the web browser.

Output type:

Specify the delivery of the PDF content.

Render at:

Validation Output

Specify how validation messages are displayed.

Reporting:

Specify the location of validation messages.

Position:

Specify the border size in pixels when the Reporting setting is Frame

Border size:

Internationalization

Select the language used for validation messages.

Language:
Chinese, Simplified (P.R.C.)
Chinese, Traditional (Hong Kong)
Chinese, Traditional (Taiwan)
Croatian (Republic of Croatia)
Czech (Czech Republic)
Danish (Denmark)
Dutch (Belgium)

Specify the character set used to encode the output stream.

Character set:

Locations

Specify the location for form resources such as images or scripts.

Base URL:

Specify the web root of Forms ES web application.

FS web root URI:

Specify the location to access application-specific web content.

Web root URI:

Specify the location of the repository from which forms are retrieved.

Content root URI:

Specify the location for the XCI configuration file.

XCI configuration URI:

Specify the location for the font mapping file.

Font map URI:

Specify the seed PDF file for optimized delivery.

Seed PDF file:

HTML Digital Signature Settings

Specify whether Digital Signature should be enabled for HTML forms.

HTML Digital Signature Enabled

Forms Cache Control Settings

For each request, server would validate related cache objects:

Unconditionally

Only if their last validation was done prior to cache check point time

Last check point time: 04-Nov-2008 14:02:02

Performs cache reset (Clears off entire cache).

Cache was last reset at: 12-Mai-2009 14:45:50

Global Cache Settings

Specify max size of the document to keep in cache. A change in this setting requires Service restart to take effect.

Max Cache Document Size (KB):

Specify whether forms are cached for subsequent retrieval.

Form Rendering Cache Enabled

In Memory Template Cache

Specify the template configuration cache size. A change in this setting requires Service restart to take effect.

Template Configuration Cache Size:

Specify the template cache size. A change in this setting requires Service restart to take effect.

Template Cache Size:

Specify whether in memory cache should be enabled. A change in this setting requires Service restart to take effect.

Enabled

In Memory Form Rendering Cache

Specify the cache size. A change in this setting requires Service restart to take effect.

Cache Size:

Specify whether in memory cache should be enabled. A change in this setting requires Service restart to take effect.

Enabled

Template Resource Cache Settings

Resource level cache settings.

Resource Caching:

Specify the cleanup interval after which the stale cached resources will be removed. A change in this setting requires Service restart to take effect.

Cleanup Interval (Seconds):

Font Embedding Settings

Comma separated list of fonts to always embed

Always Embed Fonts:

Comma separated list of fonts to never embed

Never Embed Fonts:

XCI Settings

Check this option to use system default XCI configurations.

Use system default XCI options

Check this option to use object stream compression.

Use object stream compression